

整燙系列 FUSING PRESS SERIES

連續式黏合機 OP-900/A/L/LA/1000/A/L/LA CONTINUOUS FUSING PRESS MACHINE

用途:

- ★ 針對平織/針織裁片之黏合工作。
- ★ 整匹布之黏合工作 (可搭配送/收料裝置)。

優點:

- ★ 提高產能, 連續黏接一貫作業, 最高生產效率。
- ★ 黏合寬度900mm/1000mm, 長度無限。
- ★ 自動皮帶修正裝置, 確保上、下皮帶不偏離。
- ★ 電子恆溫儀及固態繼電器控制恆溫系統, 溫度偏差至最小極限。
- ★ 加熱監控設備, 控制發熱系統正常操作。
- ★ 有6組電熱管, 加熱系統傳熱均勻各種布料均可使用。

- ★ 進口鐵氟龍黏合皮帶確保溫度均勻。
- ★ 裝有防燃滾筒可處理各種布料。
- ★ 配有網帶輸送系列, 冷卻效果佳。
- ★ 配有自動冷卻定溫停機裝置。
- ★ 強力彈簧/氣壓加壓裝置。
- ★ 自動翻轉滾片, 更替易於維護裁片。
- ★ 特殊設計之清潔布桿, 徹底清潔皮帶, 更換更容易。
- ★ 選購: A氣壓式; L皮帶加長。



Application:

- ★ For the woven/knitted fabrics fusing
- ★ Fusing for the whole roll of fabric and interline. Machine can work together with feeding conveyor and collecting stacker as option.

Feature:

- ★ Continuous fusing system increases the productivity.
- ★ The fusing width is 900/1000mm and the length is endless.
- ★ PCB and micro switch control the upper & lower belts automatically.
- ★ Electronic thermostat and the relay controller to offer the stable temperature and minimum the temperature differences to the minimum.
- ★ The heating areas are well monitored, to ensure the heating system working normally.
- ★ There are 6 heaters to distribute the heat evenly and can be used to all fabrics.
- ★ The best quality of Teflon belt assures the precise temperature.
- ★ With the wrinkle-free silicone roller to handle with all fabrics in perfect bonding.
- ★ With the cooling fan and mesh conveyor belt, which has the best cooling effect.
- ★ Auto cooling Function is automatically started once machine is switched to power off.

- ★ Standard with strong spring-pressure mechanism. No extra air-compressor is needed.
- ★ Rotary Strip-off device for strengthening the stripping function to avoid transforming on the finished fabrics.
- ★ Special-designed clean rod to clean the belt completely, and it is easy for replacement once the rod gets dirty.
- ★ Optional: A: Air (Pneumatic) Pressure L: Longer bottom belt

規格 Specification

型號 Model	OP-900/A	OP-900/LA	OP-1000/A	OP-1000/LA
電壓 Power Supply	3P 220V/380V			
馬達功率 Motor	0.24KW			
電熱功率 Heater	12KW	12.6KW	14.4KW	15KW
最大壓力 Max Pressure	5kg/cm ²			
設定溫度 Temperature	0-200℃			
黏合寬度 Fusing Width	900mm		1000mm	
黏合時間 Fusing Time	5-30secs			
供氣空壓 Supply Air Pressure	最小消耗量 Min. Consumption 5-10L/H			
機器尺寸 L×W×H Dimensions(mm)	3310×1660×1420	3310×1660×1420	3310×1750×1420	3310×1750×1420
裝箱尺寸 L×W×H Packing Volume(mm)	2300×1640×1520	2460×1640×1520	2300×1730×1510	2500×1730×1510
淨重/毛重 N.W / G.W	660/720kgs		790/860kgs	