www.china-supreme.com

## 为时尚产业 **提供智能制造解决方案**

Intelligent manufacturing Solutions for fashion industries

SP-K1-03
一次性一拖一口罩机
One plus one disposable face mask making machine

-次性平面口罩
3 Layers disposable mask

一次性平面口罩(三层)原材料上料,全程自动化控制,压片成型、上鼻梁条、超声波焊耳带,收料计数。

一次性成品下线,效率达55-60片/分钟

Disposable face mask (3 layers)material loading, whole process automated control, piece formed, nose pin mounted, ultraonic welding ear loop, collector counting, finish products once off production line, efficiency 55-60pcs/min







## 产品特点 **Features**

- 伺服系统控制,设备稳定性高,故障率低; Servo control system improves efficiency and decrease defect
- 拉筒入料,定位更精准,可使原材料宽度控制到最小,节约成本。 Feeding by roll improves accuracy of position, minimizes width of material and saves cost
- 变频控制,可根据实际需要调节设备运行速度。 Speed is adjustable by alternative-frequency
- 自动计数,成品长度尺寸控制统一,偏差±1mm,可有效控制成品长度 Automatic counting, tolerance +/- 1mm, uniform size, controllable length
- 口罩片精准送料至焊耳机输送料架 Accurate mask pieces feeding to the coneyor
- 耳带定位精准,超声波焊接,一个口罩四个焊点一次性完成。 Ultrasonic welding, 4 points welding complete in one time



平面切片 Cutting pieces



压花轮机构 Compressing mechanism



折料机构 Folding mechanism



精准送料机构 Accurate feeding mechanism



触摸操作屏 Touch screen



剪刀机构 sissoring mechanism



超声波焊接机构 Ultrasonic welding mechanism



收料输送带机构 Collector conveyor mechanism

## 规格 **Specification**

型 <del>号</del>	Model	K1-03
口罩规格	Face Mask Specification	175×95 mm
长×宽×高	Machine size	切片机: 4000×710×2000 (mm)
		焊耳带机: 2950×1400×1520 (mm)
料卷直径	Fabric Roll	76~600 mm
超声波	Ultrasonic	20 KHZ
电源	Power	单相220V 50HZ
气压	Air Pressure	0.5 Mpa、1.8L/min
占地面积(长×宽)	Footprint	4650×2900 mm
重量	Weight	380kg

以上型号仅供参考,详细情况请咨询当地经销商。 The above types are only for referen

nce, and you can consult local distributors for details

为了改良,产品规格若有变更,恕不另行通知。为安全起见,使用之前,请仔细阅读使用手册。